

PRODUCT SURVEILLANCE **CERTIFICATE**

Certificate No.:

10000443342-PA-ACCREDIA-ITA

19 March, 2021

19 March, 2021 - 18 March, 2024

This certificate consists of 3 pages

This is to certify that the final assessment process of:

VALVOROBICA INDUSTRIALE S.p.A

Via Giovanni Falcone, 2 – 24050 Zanica BG- Italy

has been monitored and found to comply with respect to the conformity assessment procedure described in:

ANNEX III MODULE A2 OF DIRECTIVE 2014/68/EU ON PRESSURE **EQUIPMENT**

This certificate is valid for the following scope:

Type of Pressure Equipment **Product Name Product Identification**

Pressure Accessory Butterfly valves Wafer type butterfly valves Lug type butterfly valves

Place and date: Vimercate, 26 March, 2021





For the issuing office: Notified Body 0496, Italy

DNV GL Business Assurance Italia S.r.I.

Nicola Privato

Management Representative



Certificate No.: 10000443342-PA-ACCREDIA-ITA Place and date: Vimercate 26 March, 2021

Jurisdiction

Application of Directive 2014/68/EU and Decreto Legislativo n. 26 of 15 February 2016.

Certificate history:

Revision	Description	Issue Date
00	Original Certificate	26 March, 2021

Products covered by this certificate

Product name	Product description	Pressure rating / Dimensional range	PED category
	Wafer type butterfly valves Wafer type butterfly valves Lug type butterfly valves Lug type butterfly valves	PN10 / Up to DN 600 PN16 / Up to DN 600 PN10 / Up to DN 600 PN16 / Up to DN 600	Up to II

Sites covered by this certificate

Site Name	Site Address	Monitored by	Date	Report ref
	Via Giovanni Falcone, 2 24050 Zanica BG- Italy	Milan/PA	04-05 March, 2021	SC222896-20210304-II- C-MRG.

Applications/limitations

Body material and min/max allowable temperature:

- EN 1563 EN-GJS-400-15 -10 °C to 200 °C;
- EN 1563 EN-GJS-400-18 -10 °C to 200 °C.

Temperature limitations:

- For butterfly valves with NBR seal max. design temperature shall be +80 °C;
- For butterfly valves with EPDM seal max. design temperature shall be +130 °C;
- Fluids: Group 2 liquids Up to DN 600,

Group 2 Gas only air, nitrogen and steam for DN 32 to DN 300,

Group 1 liquids Up to DN 600

The butterfly valves in object are pressure accessories used to control the flow-rate in a pipeline, the end of line function is excluded.



Certificate No.: 10000443342-PA-ACCREDIA-ITA

Place and date: Vimercate 26 March, 2021

Revision No.: 00

Documents reviewed:

Document No	Rev	Date	Title	Status*)
TCF007	3	23/01/2021	Technical construction file for butterfly valves	FI
Att.1	3	23/01/2021	Assembly drawings of butterfly valves: F701-DN350-VISW-00, F701-(DN400-600) VISW-00 Ed. 03 del 23/01/2021 F702-DN350-VISW-00, F702-(DN400-600)VISW-00 Ed. 03 del 23/01/2021 F705-(DN32-300)-VISS-00, F705-(DN32-300)VISW-00 Ed. 03 del 23/01/2021 F706-(DN32-300)-VISS-00, F706-(DN32-300)VISW-00 Ed. 03 del 23/01/2021	工
Att.2 - MAN006	3	23/01/2021	User/operating instructions Manual	FI
Att.3 - TCF009	3	23/01/2021	Essential Safety requirements check list ESR	FI
Att.4 - 21	3	23/01/2021	Procedura Processo di produzione- Assemblaggio valvole a farfalla	FI
Att.5 - 20	3	12/2012	Istruzione operativa collaudo valvole a farfalla con macchina banco prova matricola PC218	FI
Att.6 - 11	4	02/2021	Istruzione operativa- Piano di controllo in ingresso per le valvole a farfalla a marchio Valvorobica	FI
Att.7	3	//	Dichiarazione di conformità (draft/facsimile)	FI

^{*)} A=Approved, FI=For information

Terms and conditions

Valid terms and conditions are found in the DNV's PED Certification Requirements

End of Certificate